

SPECIFICATIONS

STYLE NAME: ENCOMPASS™	APPROX. WEIGHT PER CARTON: 27.38 LBS.
RECOMMENDED END USE: RESIDENTIAL, COMMERCIAL	CARTON SIZE: 8.68" W X 48.27" L X 2.73" H
WEAR RESISTANCE: AC3 CLASS 31	CARTONS PER PALLET: 68
BEVEL: 4 SIDED PAINTED MICRO BEVEL	SQUARE FEET PER PALLET: 1,264.8 SQ. FT.
NOMINAL PRODUCT THICKNESS: 10MM TOTAL (8MM + 2MM PAD)	APPROX. WEIGHT PER PALLET: 1,900 LBS.
NOMINAL PLANK SIZE: 8.03" W X 47.64" L X 0.55" H	PALLETS PER 40 FT. CONTAINER: 22
UNIQUE PLANKS PER SKU: 7	SQUARE FEET PER 40 FT. CONTAINER: 27,825.6 SQ. FT.
PLANKS PER CARTON: 5	APPROX. WEIGHT PER 40 FT. CONTAINER: 41,799.91 LBS.
SQUARE FEET PER CARTON: 18.6 SQ. FT.	COUNTRY OF ORIGIN: MANUFACTURED IN USA WITH GLOBAL COMPONENTS

PERFORMANCE

CARB PHASE II: TSCA Title VI Compliant	NALFA 3.9 CHAIR RESISTANCE: CLASS 3
ASTM E648 CRITICAL RADIANT FLUX: CLASS 2	NALFA 3.1 STATIC LOAD: CLASS 2
ASTM E662 SMOKE DENSITY: UNDER 450	NALFA 3.5 LARGE BALL IMPACT RESISTANCE: CLASS 2
NALFA 3.3 XENON LIGHT RESISTANCE: CLASS 2	NALFA 3.6 SMALL BALL DART IMPACT: CLASS 2
NALFA 3.4 CLEANABILITY - STAIN RESISTANCE: CLASS 2	AATCC 134 (STEP) ELECTROSTATIC: 1.0 K.V.
NALFA 3.7 WEAR RESISTANCE: CLASS 2	NALFA 3.2 THICKNESS SWELL: CLASS 2
NALFA 3.10 SURFACE BOND: CLASS 2	NALFA 3.2 THICKNESS SWELL: CLASS 2
NALFA 3.8 DIMENSIONAL TOLERANCE: CLASS 2	NALFA LF-01-2011 CONFORMANCE TESTING: CLASS 2

INSTALLATION

END USE: RESIDENTIAL, COMMERCIAL	SUITABLE GRADE LEVEL: ALL GRADES WHERE EXCESSIVE MOISTURE CONDITIONS DO NOT EXIST
INSTALLATION METHOD: FLOAT	RADIANT FLOOR HEAT COMPATIBLE: FLOOR SURFACE TEMPERATURE NOT TO EXCEED 80°F

DESIGN

PART NUMBER

EAN / UPC NUMBER

DESIGN	PART NUMBER	EAN / UPC NUMBER
CHARRED OAK 996D	62002440	190670032675
SUNSET OAK 646D	62002441	190670032682
AUTUMN ASH 369M	62002442	190670032699
PLUME OAK 909M	62002443	190670032705
THAWED MAPLE 619L	62002444	190670032712
WINTER ASH 901L	62002445	190670032729
SNOWY OAK 201L	62002446	190670032736
GOLDEN HICKORY 264M	62002447	190670032743

WARRANTIES

LIFETIME RESIDENTIAL WEAR, FADE, STAIN, JOINT & TOPICAL 24 HR MOISTURE WARRANTY

5 YEAR COMMERCIAL WEAR, FADE, STAIN, JOINT & TOPICAL 24 HR MOISTURE WARRANTY

CARE & MAINTENANCE

GENERAL MAINTENANCE SHOULD INCLUDE PLACING NON-STAINING WALK-OFF MATS AT ALL EXTERIOR ENTRANCES TO REDUCE TRACKED IN SOIL. USE A SOFT BRISTLE BROOM TO SWEEP OR VACUUM WITHOUT A BEATER BAR TO REMOVE DIRT, GRIT OR SAND.

FOR HEAVILY SOILED AREAS, USE A NON-ABRASIVE NEUTRAL PH CLEANER SPECIALLY FORMULATED FOR USE WITH LAMINATE AND A MICROFIBER MOP.