

SPECIFICATIONS

STYLE NAME: INNOVIOUS PERCEPTIONS	APPROX. WEIGHT PER CARTON: 43.43 LBS.
LOCKING SYSTEM: i4F Standard	CARTON SIZE: 9.33"W X 59.49" L X 1.61"H
FINISH: EMBOSS IN REGISTER (EIR)	CARTONS PER PALLET: 52
BEVEL: PAINTED BEVEL	SQUARE FEET PER PALLET: 1,116.96 SQ. FT.
NOMINAL PRODUCT THICKNESS: 6 MM TOTAL (5 MM + 1 MM PAD)	APPROX. WEIGHT PER PALLET: 2,324.53 LBS.
NOMINAL PLANK SIZE: 8.78" W X 58.74"L x 0.23" H	PALLETS PER 40 FT. CONTAINER: 23
UNIQUE PLANKS PER SKU: 4	SQUARE FEET PER 40 FT. CONTAINER: 25,695.99 SQ. FT.
PLANKS PER CARTON: 6	APPROX. WEIGHT PER 40 FT. CONTAINER: 110,230 LBS.
SQUARE FEET PER CARTON: 21.48 SQ. FT.	COUNTRY OF ORIGIN: MANUFACTURED IN VIETNAM

PERFORMANCE

FLOOR SCORE CERTIFIED	ASTM C1028 SCOF: DRY 0.67, WET 0.62
ORTHO PHTHALATE FREE	ASTM F970 STATIC LOAD: PASSES ≤ 250 PSI
ASTM E648 CRITICAL RADIANT FLUX: CLASS 1	ASTM F137 FLEXIBILITY: PASSES 120 MM MANDREL
ASTM E662 SMOKE DENSITY: UNDER 450	ASTM F925 CHEMICAL RESISTANCE: PASSES
ASTM F1515 LIGHT STABILITY: < 8.0 DELTA E - PASSES	ASTM F1514 HEAT STABILITY DELTA E < 8.0: PASSES
ASTM F2199 DIMENSIONAL STABILITY HEAT: PASSES	ASTM D4060 ABRASION RESISTANCE: 58,000 CYCLES
AATCC 134 (STEP) ELECTROSTATIC: 1.4 K.V. OR LOWER	ASTM D2047 COEFFICIENT OF FRICTION: DRY 0.90

INSTALLATION

END USE: RESIDENTIAL, COMMERCIAL	SUITABLE GRADE LEVEL: ALL GRADES WHERE EXCESSIVE MOISTURE CONDITIONS DO NOT EXIST
INSTALLATION METHOD: FLOAT	RADIANT FLOOR HEAT COMPATIBLE: FLOOR SURFACE TEMPERATURE NOT TO EXCEED 80°F

DESIGN

PART NUMBER

EAN / UPC NUMBER

DESIGN	PART NUMBER	EAN / UPC NUMBER
HOLLIS ELM 249M	60002077	190670034570
NOL ELM 219M	60002078	190670034587
LANDRY ELM 900L	60002079	190670034594
HONOR ELM 309L	60002080	190670034600
OLLIE OAK 140L	60002081	190670034617
ARDEN OAK 614D	60002082	190670034624
HALSTON OAK 644D	60002083	190670034631
LUX OAK 696D	60002084	190670034648
KINGSLEY OAK 239L	60002085	190670034655
RIVER OAK 199M	60002086	190670034662

WARRANTIES

LIFETIME RESIDENTIAL WEAR, FADE, STAIN, JOINT & TOPICAL 72 HR MOISTURE WARRANTY

20 YEAR COMMERCIAL WEAR, FADE, STAIN, JOINT & TOPICAL MOISTURE WARRANTY

CARE & MAINTENANCE

GENERAL MAINTENANCE SHOULD INCLUDE PLACING NON-STAINING WALK-OFF MATS AT ALL EXTERIOR ENTRANCES TO REDUCE TRACKED IN SOIL. USE A SOFT BRISTLE BROOM TO SWEEP OR VACUUM WITHOUT A BEATER BAR TO REMOVE DIRT, GRIT OR SAND.

FOR HEAVILY SOILED AREAS, USE A NON-ABRASIVE NEUTRAL PH CLEANER SPECIALLY FORMULATED FOR USE WITH LAMINATE AND A MICROFIBER MOP.