

AN EVOLUTION IN DESIGN. FLOORING FOR A NEW GENERATION.

# High Street™

LUXURY VINYL FLOORING



ARIA | IRON | 60083

## A vinyl sheet flooring collection designed with Main Street in mind.

High Street™ offers the best of both worlds — the durability needed for light commercial applications and the stylish designs to suit any decor.

With the Techtonic™ Technology protective coating, you'll get increased durability and better performance to keep your floor looking better and lasting longer. In controlled lab tests, High Street™ outperformed the market leader with:

- **More scratch resistance**
- **More stain resistance**
- **25% more abrasion resistance**

High Street™ is not only functional, it's also stylish. Whether you want a modern and sleek aesthetic, a cozy and welcoming feel, or anything in between, we have options to suit any taste.



 **Tarkett**  
*Home*

# High Street™

LUXURY VINYL FLOORING



**60001 | Oslo**  
Pewter  
48" x 72" DNR



**60011 | Corbin**  
Latte  
36" x 72" DNR



**60021 | Markham**  
Wheat  
36" x 36", 18" Drop, DNR



**60031 | Ozart**  
Greige  
36" x 36", 18" Drop, REV



**60041 | Rowell**  
Bisque  
36" x 72" DNR



**60051 | Sedwick**  
Chai  
36" x 72" DNR



**60052 | Sedwick**  
Kobicha  
36" x 72" DNR



**60061 | Monroe**  
Sunkiss  
48" x 72", Drop 24", DNR



**60062 | Monroe**  
Chestnut  
48" x 72", Drop 24", DNR



**60071 | Strata**  
Cashmere  
36" x 36" DNR



**60072 | Strata**  
Madras  
36" x 36" DNR



**60081 | Aria**  
Glacier  
36" x 36", Drop 18", DNR



**60082 | Aria**  
Lunar  
36" x 36", Drop 18", DNR



**60083 | Aria**  
Iron  
36" x 36", Drop 18", DNR



**60091 | Baxton**  
Limestone  
36" x 72" DNR



**60092 | Baxton**  
Earth  
36" x 72" DNR

Specifications	
Series	60XXX
Nominal Total Thickness	80 mils (0.08"/2.03mm)
Wear Layer Thickness	20 mils (0.02"/0.51mm)
Wear Layer Finish	Urethane (Low Gloss), Techtonic™ Technology
Width	12' (3.6m)
Standard Roll Size	100 sq. yd. (83.61 m <sup>2</sup> )
Weight per Sq. Yd.	4.81 lbs. (2.18 kg)
ASTM F1303	Type I, Grade 1, Class C
ASTM F925 (Stain Resistance)	Passes
ASTM D2047 (Slip)	>0.5
ASTM E648 (Fire)	>.45 W/cm <sup>2</sup>
ASTM E662 (Smoke)	<450
ASTM F137 (Flexibility)	Passes
ASTM F970 Static Load Limit	175 lbs./sq. in. (12.3 kg/cm <sup>2</sup> )
ASTM F1514 (Heat Stability)	Δ E < 8
ASTM F1515 (Light Stability)	Δ E < 8
ASTM E2179 (Impact Sound Reductions)	Δ IIC 13 dB
Location	Below, on and above grade concrete, above grade plywood
Adhesive	Tarkett® QBond-One™
Seam Sealer	Tarkett DT-65 Seam Sealer (Low Gloss)
HUD/FHA Minimum	Meets Wearlayer Thickness
FloorScore® Certification	SCS-FS-02746
CERTIFIED <b>asthma &amp; allergy friendly</b> * by Allergy Standards Ltd and the Asthma and Allergy Foundation of America (AAFA)	Certificate AAFC: 1880/16/05/01/2066

**High Street™ floors are built to last, making it the ideal floor exclusively for Main Street customers.**

©2023 Tarkett North America 09/2023



Tarkett Home is distributed by William M. Bird



The CERTIFIED ASTHMA & ALLERGY FRIENDLY Mark is a Registered Certification Mark of ALLERGY STANDARDS LTD and the ASTHMA AND ALLERGY FOUNDATION OF AMERICA.

For more accurate color and pattern representation, we suggest you visit an authorized Tarkett Home dealer to view an actual product sample.