

RIGID. FLEXIBLE. BEAUTIFUL.

# NuGen™

RIGID CORE FLOORING



BARREL AGED | MAPLE | 270293016

## Use in Any Room

Waterproof so it's safe to use in kitchens, bathrooms, or laundry rooms.

## Install Immediately

No acclimation time required. Buy and install immediately after purchase.

## Fast and Easy to Install

NuGen's fast-locking click system ensures a low-cost, low-mess installation – even over existing floors! No power tools required.

## Durable

Stands up to kids, pets, high heels and heavy furniture.

## Quiet Under Foot

The acoustical backing provides superior sound absorption and overall comfort.

## Finish with Style

Finish the install with coordinating trims and moldings to help your customer create a seamless, cohesive look. We also offer **matching** flush stair treads and returns with VersaCap™, made from the actual floor!



WATERPROOF



EASY TO INSTALL



DURABLE



PET & FAMILY FRIENDLY



SCRATCH & DENT RESISTANT



COMFORTABLE & QUIET


 **Tarkett**  
*Home*

# NuGen™

RIGID CORE FLOORING



**Cape Cod**  
Hartford  
270293013



**Burning Oak**  
Whitewashed  
270293014



**Cape Cod**  
Bennett Grey  
270293015



**Barrel Aged**  
Maple  
270293016

**New**



**Sparrow Oak**  
Gray Pearl  
270285002



**Chestnut Ridge**  
Furrowed  
270285005



**Pecan Flame**  
Claro  
270285006



**Lacebark Elm**  
Wheat  
270293004



**Black Walnut**  
Spiced  
270293006



**Pin Oak**  
Drift  
270293007

Specifications		
Size	7" x 48" (181mm x 1220mm)	7" x 60" (181mm x 1520mm)
Pieces per Carton	12 Planks	10 Planks
Weight per Carton	Planks: 39.47 lbs. (17.9 kgs.)	Planks: 43.4 lbs (19.68 kgs.)
Area per Carton	28.52 sq. ft. (2.65m <sup>2</sup> )	29.61 sq. ft. (2.75m <sup>2</sup> )
Cartons per Pallet	55	45
Nominal Thickness	0.177" (4.5mm)	
Wear Layer Thickness	12 mils/.012"	
IXPE Acoustical Backing	0.039" (1mm)	
Finish Edge	Square	
Finish	Polyurethane	
Material	Ortho-Phthalate Free, 100% Virgin Material	
Reusable Content	100% Reclaimable	
Scratch/Scuff/Abrasion Properties	Excellent	
ASTM F3261 (Rigid Polymeric Core) Specification	Class 1, Type A, Grade 2, Backing Class B	
Dimensional Stability	ASTM F2199 Passes	
Static Load Limit	ASTM F970 Passes at 250 PSI	
Residual Indentation	ASTM F1914 Passes	
Slip Resistance	ASTM D2047 ≥ 0.5 SCOF	
Fire	ASTM E648 ≥ .45 w/cm <sup>2</sup>	
Heat Stability	ASTM F1514 Δ E ≤ 8	
Light Stability	ASTM F1515 Δ E ≤ 8	
Staining	ASTM F925 Passes	
Installation System	Click System: UniClick®	
Certification	FloorScore® and Assure Certified™	



Tarkett Home is distributed by William M. Bird



For more accurate color and pattern representation, we suggest you visit an authorized Tarkett Home dealer to view an actual product sample.